

EFI-P2 A 16/0.03



Specificatii

Cod ETI	002061110
Descriere	EFI-P2 A 16/0.03
Denumire clasă	Diferențial RCCB
Curent nominal (A)	16
Tip	A
Curent de defect nominal (A)	0.03
Tip curent	A
Tensiunea nominală(V)	240
Tip montaj	TH 35
Adâncime (mm)	68
Număr de poli	1+N
Grad de protecție IP	IP20
Frecvență nominală (Hz)	50/60
Standarde	IEC/EN 61008
Secțiune transversală nominală	1-25
Timp de declansare	Undelayed
Curent nominal de scurtcircuit Inc (kA)	10

[Pagina de produse online](#)



Alta documentatie

[Catalog caracteristici tehnice](#)[Certificate](#)[Model 3D](#)[Manual de instructiuni](#)[Declaratie CE](#)[COM_ETISTORE_ITEM_DOCTYPE_whitePa
per](#)[Eplan mușchi](#)

ETIM clasificare internationala

Clasificare	EC000003
Denumire clasă	Residual current circuit breaker (RCCB)
Number of poles	2
Rated voltage	240V
Rated current	16A
Rated fault current	30mA
Mounting method	DIN rail
Leakage current type	A
Selective protection	
Short-time delayed tripping	
Short-circuit breaking capacity (I _{cw})	10kA
Surge current capacity	0,4kA
Frequency	50/60 Hz
Additional equipment possible	1
Degree of protection (IP)	IP20
Width in number of modular spacings	2
Built-in depth	68mm
Connectable conductor cross section multi-wired	1...25mm ²

Desen cotat



Schema de conexiuni

